

### Claims

1. Assembly of a peg (1) and of a sleeve (30)  
of a component (11) and of a support (10) which  
5 are intended to be push-fitted one into the  
other to fix the component (11) to the support  
(10), the peg (1) comprising an anterior portion  
(2) to be introduced with clearance into the  
sleeve (30) and a posterior fixing part (3),  
10 characterized in that the posterior part (3) of  
the peg (1) is designed to compensate for the  
clearance.

2. Assembly according to claim 1, in which the  
15 diameter of the posterior fixing part (3) of the  
peg (1) is greater than the diameter of the  
sleeve (30), and the peg (1) is slotted (8).

3. Assembly according to claim 2, in which the  
20 peg (1) has lateral flats (9).

4. Assembly according to claim 3, in which the  
posterior fixing portion (3) comprises a  
cylindrical part (4).

25

5. Assembly according to claim 4, in which the posterior fixing portion (3) comprises a part (5) that does not compensate for the clearance.
- 5 6. Assembly according to claim 5, in which the part (5) that does not compensate for the clearance is frustoconical and situated behind the cylindrical part (4).
- 10 7. Assembly according to claim 6 in which the peg (1) is coated with a graphite deposit.
8. Assembly according to claim 7 intended to fix an inertial unit (11) to a rack (10).